QUEST INDUSTRIAL PRODUCTS

SAFETY DATA SHEET

1. Identification

GHS product identifier SUPER GLOSS SPRAY AC-512/C

Product Code 01442 100133 604

Version # 03

Issue date 05-24-2016
Revision date 05-24-2016
Supersedes date 05-24-2016
CAS # Mixture
Recommended use Not available.

Recommended Restrictions Not available.

ManufacturerQuest Industrial Products, LLC.informationN92 W14701 Anthony Avenue

Menomonee Falls

United States info@quest-ip.com

General Assistance (800) 966-7580 Chemtrec Phone (800) 424-9300

2. Hazards identification

GHS classification

Physical hazardsAerosolsCategory 1Health hazardsAcute toxicity, oralCategory 4Skin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2A

Reproductive toxicity (the unborn child)

Category 2

Specific target organ toxicity, single exposure

Category 3 narcotic effects

Specific target organ toxicity, repeated

Category 2

exposure

Environmental hazards Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment,

long-term hazard

Category 3

Category 3

GHS label elements

Signal word Danger







Hazard statement

Extremely flammable aerosol. Pressurized container: May burst if heated. Harmful if swallowed. Causes skin irritation. Causes skin and eye irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face

protection.

01442 100133 604 Version #: 03 Revision date: 05-24-2016 Issue date: 05-24-2016

Response IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. IF ON SKIN: Wash with

plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated

clothing and wash it before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards which do not result in classification

None known.

Supplemental information 54.44% of the mixture consists of component(s) of unknown acute oral toxicity. 78.78% of the

mixture consists of component(s) of unknown acute hazards to the aquatic environment. 78.78%

of the mixture consists of component(s) of unknown long-term hazards to the aquatic

environment

3. Composition/information on ingredients

Components	CAS#	Percent
ACETONE	67-64-1	20 - < 30
TOLUENE	108-88-3	20 - < 30
N-BUTANE	106-97-8	10 - < 20
PROPYLENE GLYCOL METHYL ETHER ACETATE	108-65-6	10 - < 20
Other components below reportable levels		20 - < 30

4. First aid measures

First aid procedures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Eye Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Get medical advice/attention if you feel unwell.

Most important symptoms and effects, both acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

cause redness and pain. Prolonged exposure may cause chronic effects.

Notes to physician Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim

under observation. Symptoms may be delayed.

General advice IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice

(show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in

attendance.

5. Fire-fighting measures

Suitable extinguishing media

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

illeula

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

During fire, gases hazardous to health may be formed.

Protective equipment and precautions for firefighters

Protection of fire-fighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

ado sinicia, gioves, rabber boots, ana in enclosed spaces, cobrt.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose

holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

General fire hazards

Extremely flammable aerosol.

containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

6. Accidental release measures

Personal precautions Keep unne

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Methods for containment

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area)

Methods for cleaning up

Ventilate the contaminated area. Wear appropriate protective equipment and clothing during clean-up. Prevent product from entering drains. Stop the flow of material, if this is without risk. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

7. Handling and storage

Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist or vapor. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Storage

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls / personal protection

Control parameters

US. ACGIH Threshold Limit Values

Components	Туре	Value	
ACETONE (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
N-BUTANE (CAS 106-97-8)	STEL	1000 ppm	
TOLUENE (CAS 108-88-3)	TWA	20 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
ACETONE (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
TOLUENE (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

^{* -} For sampling details, please see the source document.

Recommended monitoring procedures

Follow standard monitoring procedures.

Engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection Wear appropriate chemical resistant clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Color
Form
Aerosol.

Odor
Not available.

Odor threshold
Not available.

PH
Not available.

Melting point/Freezing point-305.68 °F (-187.6 °C) estimatedBoiling point-43.78 °F (-42.1 °C) estimatedFlash point-156.0 °F (-104.4 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Flammability limits in air, 1.3 % estimated lower, % by volume

Flammability limits in air, upper, % by volume

12.8 % estimated

Vapor pressure 2076.02 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water)Not available.Partition coefficientNot available.

(n-octanol/water)

Auto-ignition temperature 550 °F (287.78 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Specific gravity 0.75

VOC 457.59 g/l Material

4.97 lbs/gal Regulatory 595.9 g/l Regulatory 3.82 lbs/gal Material

Percent volatile 85.31

Density 6.27 lbs/gal

Other data

Explosive properties Not explosive.

Heat of combustion (NFPA

30B)

28.62 kJ/g estimated

Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

Material name: SUPER GLOSS SPRAY AC-512/C 01442 100133 604 Version #: 03 Revision date: 05-24-2016 Issue date: 05-24-2016

11. Toxicological information

_					
	AVI	\sim	\sim	1001	A 2 t 2
	UXI	CU	υu	ıcaı	data

Toxicological data			
Components	Species	Test Results	
ACETONE (CAS 67-64-1)			
<u>Acute</u>			
Dermal	D 1111	"	
LD50	Rabbit	> 15800 mg/kg	
Inhalation			
LC50	Rat	76 mg/l, 4 Hours	
Oral			
LD50	Mouse	3000 mg/kg	
	Rat	5800 mg/kg	
N-BUTANE (CAS 106-97-8)			
<u>Acute</u>			
Inhalation			
LC50	Mouse	680 mg/l, 2 Hours	
	Rat	658 mg/l, 4 Hours	
TOLUENE (CAS 108-88-3)			
<u>Acute</u>			
Dermal			
LD50	Rabbit	12124 mg/kg	
		14.1 ml/kg	
Inhalation			
LC50	Mouse	5320 ppm, 8 Hours	
		400 ppm, 24 Hours	
	Rat	26700 ppm, 1 Hours	
		12200 ppm, 2 Hours	
		8000 ppm, 4 Hours	
Oral		урги, т.т.ож.о	
LD50	Rat	2.6 g/kg	
	Inhalation. Ingestion. Skin co		
Routes of exposure	•	•	
Toxicological information		substance or mixture may cause adverse effects.	
Acute toxicity	Harmful if swallowed. Narcot	C ETTECIS.	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Causes serious eye irritation		
Respiratory sensitizer	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected	to cause skin sensitization.	
Mutagenicity	No data available to indicate mutagenic or genotoxic.	product or any components present at greater than 0.1% are	
Carcinogenicity			
ACGIH Carcinogens			
ACETONE (CAS 67-64- TOLUENE (CAS 108-88		A4 Not classifiable as a human carcinogen. A4 Not classifiable as a human carcinogen.	
,	Evaluation of Carcinogenicity		
TOLUENE (CAS 108-88	·	3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	Suspected of damaging the	- · · · · · · · · · · · · · · · · · · ·	
Specific target organ toxicity - single exposure	May cause drowsiness and o		
Specific target organ toxicity - repeated exposure	May cause damage to organ	s through prolonged or repeated exposure.	
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may		
	be harmful.		

Material name: SUPER GLOSS SPRAY AC-512/C

SDS GHS UN

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

12. Ecological information

Ecotoxico	Ivuical	ctch
LCOLOXICO	ıogıcaı	uata

Components		Species	Test Results
ACETONE (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
TOLUENE (CAS 108-88-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours

Ecotoxicity Harmful to aquatic life with long lasting effects.

Harmful to aquatic life with long lasting effects. An environmental hazard cannot be excluded in the **Environmental effects**

event of unprofessional handling or disposal.

Persistence / degradability No data is available on the degradability of this product.

Bioaccumulation

Bioaccumulative potential

Octanol/water partition coefficient log Kow

ACETONE -0.24**N-BUTANE** 2.89 **TOLUENE** 2.73

Harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment. **Aquatic toxicity**

Mobility No data available for this product.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal methods Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

ADR

UN number

UN proper shipping name

Transport hazard class(es)

Aerosols, Flammable

Class 2.1 Subsidiary risk 2.1 Label(s)

Not available. Hazard No. (ADR) **Tunnel restriction code** Not available. Not applicable. Packing group

Environmental hazards

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

RID

1950 **UN number**

UN proper shipping name Transport hazard class(es)

Aerosols, Flammable

Class

Material name: SUPER GLOSS SPRAY AC-512/C

SDS GHS UN

Subsidiary risk 2.1 Label(s)

Packing group Not applicable.

Environmental hazards No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

1950 **UN** number

Aerosols, Flammable **UN proper shipping name**

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

Packing group Not applicable.

Environmental hazards

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed.

aircraft

Allowed. Cargo aircraft only

IMDG

1950 **UN** number

UN proper shipping name

Aerosols, Flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

Packing group Not applicable.

Environmental hazards

Marine pollutant No.

Not available. **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Not established.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

ADR; IATA; IMDG; RID



15. Regulatory information

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

Material name: SUPER GLOSS SPRAY AC-512/C

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.

SDS sections updated

Hazards identification: Hazard statement

GHS: Classification

Material name: SUPER GLOSS SPRAY AC-512/C SDS GHS UN