

1. COMPANY AND PRODUCT IDENTIFICATION

DUNCAN ENTERPRISES EMERGENCY TELEPHONE NUMBERS

5673 East Shields Avenue Health Emergency: 559-291-4444 7:00 am - 3:30 pm Fresno, CA 93727

Pacific Standard Time

559-291-4444 Spill and Off-Hour

559-291-9444 (Fax) Health Emergencies: 800-424-9300 U.S. and Canada

> 703-527-3887 Outside U.S. and

> > Canada (Collect)

Product Name: DUNCAN COVER-COAT® OPAQUE UNDERGLAZES

Product Type: Nontoxic Ceramic Glaze

2. COMPOSITION / INFORMATION ON INGREDIENTS

The ingredients in this formulation are a trade secret. All ingredients in the formula are non-hazardous, unless specified in Sections 3 and 15.

3. HAZARDS IDENTIFICATION

HMIS Hazard Ratings for Product

Health: 0 = MinimalFlammability: 0 1 = SlightReactivity: 0 2 = Moderate See Section 8 3 = Serious Personal Protection:

4 = Severe

* = Chronic Effects

4. FIRST AID MEASURES

Flush eyes with large amounts of water until irritation subsides. Consult a physician Eye Contact:

if irritation persists.

Skin Contact: Wash affected skin areas thoroughly with soap and water. Consult a physician if

irritation persists.

Inhalation: Move subject to fresh air.

Ingestion: If swallowed, give two glasses of water to drink. Consult a physician. Never give

anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

Autoignition Temperature: Nonflammable Flash Point: Not Applicable Not Applicable **Upper Explosive Limit (%):** Lower Explosive Limit (%): Not Applicable

Extinguisher Media: Product is nonflammable – Use extinguishing

media appropriate for surrounding fire

Special Firefighting Procedures: Not Applicable Fire & Explosion Hazards: Not Applicable NFPA Flammability Hazard Class: 0 = Insignificant

Duncan Enterprises Material Safety Data Sheet - Cover-Coat Opaque Underglazes

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Spills should be taken up with suitable absorbent material and placed in

containers. Spill areas can be washed with water; collect wash water for

approved disposal. Do not flush to storm sewer or waterway.

For safety and environmental precautions, please review entire Material Safety Data Sheet for necessary information.

7. HANDLING AND STORAGE

Storage Temperature: 40° - 100°F

Handling / Storage: Protect from freezing; keep container sealed when not in use

Ventilation Requirements: General

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Conditions Under Which Personal Protective Equipment Required

Eye Protection Requirements: Wear safety glasses with side shields

Glove Requirements: Gloves are not normally required for foreseeable

conditions of use

Clothing Requirements: Protective clothing is normally not necessary for

foreseeable conditions of use

Change / Removal of Clothing: None required

Wash Requirements: Good hygiene practices should be followed

Respirator Requirements: NIOSH approved respirator for sprays and mists recommended

if using a sprayer

Ventilation Requirements: General; local exhaust ventilation recommended when spraying

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance / Physical Description: Colored liquid. Odorless

pH: 7 - 10
Boiling Point: 212°F
Freezing Point: 32°F
Melting Point: 1800°F
Solubility in Water: Miscible
Specific Gravity (Water = 1): 1.3 - 1.8

Bulk Density: 10.8 – 15.0 lb / gal

Evaporation Rate (Water = 1):

Vapor Pressure: 17.5 mm Hg @ 20°C (68°F)

Autoignition Temperature:Not ApplicableFlash Point:Not ApplicableOxidizing Properties:Not Applicable

Duncan Enterprises Material Safety Data Sheet - Cover-Coat Opaque Underglazes

10. STABILITY AND REACTIVITY

Stability:StableIncompatible Materials:None knownNFPA Reactivity Hazard Class:0 = Insignificant

Hazardous Decomposition Products: Avoid fumes when firing

Hazardous Polymerization: Will not occur Conditions to Avoid: None Known

11. TOXICOLOGICAL INFORMATION

Short – Term Effects of Exposure

Routes of Entry: Inhalation: No Skin Contact: No Ingestion: Yes

Acute Effects – Eye: Abrasive, can scratch eyes

Acute Effects – Skin Contact: No hazard in normal industrial use.

Acute Effects – Inhalation: No hazard in normal industrial use.

Acute Effects – Ingestion: No hazard in normal industrial use.

Long - Term Effects of Exposure

Effect of Chronic Exposure: This product should be considered non – hazardous and has no known

chronic effects.

Target Organs: Not applicable

Carcinogenicity: IARC Monographs: No NTP: No OSHA Regulated: No

12. ECOLOGICAL INFORMATION

No Applicable Data

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods: Waste disposal should be in accordance with existing Federal, State,

and Local environmental regulations.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Information

DOT Shipping Name: Glazes or Stains, Ceramic or Pottery, Artists or Hobbyists Liquid

DOT Hazard Class: 88690 Sub. 1

DOT Reportable Quantity: None

Duncan Enterprises Material Safety Data Sheet - Cover-Coat Opaque Underglazes

15. REGULATORY INFORMATION

TSCA: All components are on the TSCA Inventory

FDA: 21CFR175.105

SARA/Title III: This product contains no substances at or above the reported threshold under

Section 313, based on available data.



Products bearing the Nontoxic Product Seal are certified in a program of toxicological evaluation by a nationally recognized toxicologist to contain no materials in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems. These products are certified to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236. In addition, there is no physical hazard as defined within 29 CFR Part 1910.1200(c).

16. OTHER INFORMATION

Table of Abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

ANSI American National Standards Institute
ASTM American Society for Testing Materials

°C Degrees Centigrade
CAS Chemical Abstract Service

CERCLA Comprehensive Environmental Response, Compensation and Liability Act

CFR Code of Federal Regulations
CPR Controlled Products Regulations
DOT Department of Transportation
EPA Environmental Protection Agency

°F Degrees Fahrenheit

FDA Food & Drug Administration

Hg Mercury

HMIS Hazardous Materials Identification System
IARC International Agency for Research on Cancer

LD Lethal Dose

mg / kg Milligram per kilogram

mm Millimeter

MSDS Material Safety Data Sheet

MSHA Mine Safety and Health Administration

N / A Not Applicable

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

ppm Parts per million

SARA Superfund Amendment and Reauthorization Act

STEL Short-Term Exposure Limit

Duncan Enterprises Material Safety Data Sheet – Cover-Coat Opaque Underglazes

16. OTHER INFORMATION (Continued)

Table of Abbreviations (Continued)

TSCA Toxic Substances Control Act
TWA Time - Weighted Average

U.N. United Nations

WHMIS Workplace Hazardous Materials Information System

Greater ThanLess Than

Creation Date: 07/00
Revision Date: 08/20/07
Technical Contact: Frank Peters

Senior R&D Chemist Duncan Enterprises 5673 East Shields Avenue

Fresno, CA 93727 559-291-4444 559-291-9444 (Fax)

Disclaimer

The information given and the recommendations made herein apply to our product(s) alone and not combined with any other product(s). Such are based on our research and on data from other reliable sources and are believed to be accurate. No guarantee of accuracy is made. It is the purchaser's responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.